



CLIP	LENGTH		WIDTH		HEIGHT		INSIDE		OUTSIDE		CLIPS/ CTN	CLIPS/ ROLL	WT./CTN		WT./ROLL	
	IMP	MET	IMP	MET	IMP	MET	IMP	MET	IMP	MET			LBS	KG	LBS	KG
52A14	.520	13.21	.430	10.92	5/16	7.94	.148	3.76	.206	5.23	15,080	15,000	27.67	12.55	27.53	12.49
52A14_G	.520	13.21	.430	10.92	5/16	7.94	.142	3.61	.206	5.23	15,080	15,000	27.67	12.55	27.53	12.49
64A18_G	.640	16.26	.430	10.92	13/32	10.32	.196	4.98	.260	6.60	10,340	15,000	25.77	11.69	37.38	16.96
68H17_LP	.680	17.27	.860	21.84	7/16	11.11	.185	4.70	.260	6.60	--	6,500	--	--	35.50	16.10
68H18	.686	17.42	.860	21.84	15/32	11.90	.196	4.98	.260	6.60	4,700	6,460	25.10	11.39	34.51	15.65
68H18_C	.686	17.42	.860	21.84	15/32	11.90	.182	4.62	.260	6.60	4,700	6,460	25.10	11.39	34.51	15.65
71A18	.708	17.98	.430	10.92	7/16	11.11	.202	5.13	.260	6.60	9,400	13,025	23.49	10.66	32.54	14.76
72E18	.720	18.29	.670	17.02	15/32	11.90	.202	5.13	.260	6.60	6,110	--	24.19	10.97	--	--
74F18R	.736	18.69	.735	18.67	1/2	12.70	.196	4.98	.260	6.60	--	7,710	--	--	37.77	17.13
74F18S	.736	18.69	.735	18.67	1/2	12.70	.202	5.13	.260	6.60	5,076	--	22.53	10.22	--	--
74F18_C	.736	18.69	.735	18.67	1/2	12.70	.182	4.62	.260	6.60	5,076	7,710	24.87	11.28	37.77	17.13
74F18_L	.736	18.69	.735	18.67	1/2	12.70	.188	4.78	.260	6.60	5,076	7,710	24.87	11.28	37.77	17.13
74H17_LP	.740	18.80	.860	21.84	1/2	12.70	.173	4.39	.260	6.60	4,230	6,750	29.71	13.48	47.41	21.51
74H18R	.740	18.80	.860	21.84	1/2	12.70	.196	4.98	.260	6.60	--	6,750	--	--	38.90	17.65
74H18S	.740	18.80	.860	21.84	1/2	12.70	.202	5.13	.260	6.60	4,230	--	22.09	10.02	--	--
74H18_C	.740	18.80	.860	21.84	1/2	12.70	.182	4.62	.260	6.60	4,230	6,750	24.38	11.06	38.90	17.65
74H18_G	.740	18.80	.860	21.84	1/2	12.70	.196	4.98	.260	6.60	4,230	6,750	24.38	11.06	38.90	17.65
74H18_L	.740	18.80	.860	21.84	1/2	12.70	.187	4.75	.260	6.60	4,230	3,750	24.38	11.06	38.90	17.65
76A18	.768	19.51	.430	10.92	1/2	12.70	.202	5.13	.260	6.60	8,460	13,025	22.92	10.40	35.30	16.01
76A22	.755	19.18	.430	10.92	1/2	12.70	.202	5.13	.260	6.60	--	12,300	--	--	32.77	14.86
78F18	.780	19.81	.735	18.67	15/32	11.90	.196	4.98	.260	6.60	4,320	--	22.43	10.17	--	--
78H17_LP	.780	19.81	.860	21.84	17/32	13.49	.173	4.39	.260	6.60	--	5,300	--	--	39.24	17.80
80F18_L	.800	20.32	.735	18.67	17/32	13.49	.188	4.78	.260	6.60	5,076	7,710	27.03	12.26	41.06	18.62
80F23	.800	20.32	.735	18.67	1/2	12.70	.248	6.30	.306	7.77	4,320	6,667	20.85	9.46	32.17	14.59
80H18	.800	20.32	.860	21.84	17/32	13.49	.196	4.98	.260	6.60	4,230	6,800	26.36	11.96	42.37	19.22
80H18_LP	.800	20.32	.860	21.84	17/32	13.49	.187	4.75	.260	6.60	4,230	6,800	26.36	11.96	42.37	19.22
80H23	.800	20.32	.860	21.84	1/2	12.70	.248	6.30	.306	7.77	3,600	--	20.32	9.22	--	--
83H17_LP	.830	21.08	.860	21.84	9/16	14.29	.182	4.62	.260	6.60	--	5,000	--	--	39.39	17.87
83H18	.830	21.08	.860	21.84	9/16	14.29	.194	4.93	.260	6.60	--	5,000	--	--	33.33	15.12
84F23	.840	21.34	.735	18.67	1/2	12.70	.242	6.15	.306	7.77	--	6,500	--	--	36.34	16.48
85A18	.856	21.74	.430	10.92	9/16	14.29	.202	5.13	.260	6.60	7,520	11,771	22.72	10.31	35.56	16.13
85A22	.856	21.74	.430	10.92	17/32	13.49	.230	5.84	.288	7.32	6,720	12,300	20.30	9.21	37.16	16.86
85H17_LP	.850	21.59	.860	21.84	19/32	15.08	.173	4.39	.260	6.60	--	4,325	--	--	34.89	15.83
85H18_C	.850	21.59	.860	21.84	9/16	14.29	.180	4.57	.260	6.60	3,290	4,325	22.46	10.19	29.35	13.31

CLIP	LENGTH		WIDTH		HEIGHT		INSIDE		OUTSIDE		CLIPS/	CLIPS/	WT./CTN		WT./ROLL	
	IMP	MET	IMP	MET	IMP	MET	IMP	MET	IMP	MET	CTN	ROLL	LBS	KG	LBS	KG
87F18	.870	22.10	.735	18.67	9/16	14.29	.196	4.98	.260	6.60	4,512	--	26.13	11.85	--	--
87F18_LP	.870	22.10	.735	18.67	9/16	14.29	.187	4.75	.260	6.60	4,512	--	26.13	11.85	--	--
87H17_LP	.870	22.10	.860	21.84	19/32	15.08	.173	4.39	.260	6.60	--	4,375	--	--	36.13	16.39
87H18	.870	22.10	.860	21.84	19/32	15.08	.194	4.93	.260	6.60	3,760	5,625	26.27	11.92	39.30	17.83
87H18_C	.870	22.10	.860	21.84	19/32	15.08	.180	4.57	.260	6.60	3,760	5,625	26.27	11.92	39.30	17.83
87H18_L	.870	22.10	.860	21.84	19/32	15.08	.186	4.72	.260	6.60	3,760	5,625	26.27	11.92	39.30	17.83
88A22	.881	22.38	.430	10.92	9/16	14.29	.230	5.84	.288	7.32	6,720	12,300	20.89	9.48	38.24	17.35
88A22_LP	.881	22.38	.430	10.92	9/16	14.29	.213	5.41	.288	7.32	6,720	12,300	23.77	10.78	43.51	19.74
88A23	.874	22.20	.430	10.92	9/16	14.29	.248	6.30	.306	7.77	6,400	9,375	19.75	8.96	28.92	13.12
88F23	.880	22.35	.735	18.67	9/16	14.29	.248	6.30	.306	7.77	3,840	5,521	20.38	9.24	29.31	13.30
88F23_L	.880	22.35	.735	18.67	9/16	14.29	.233	5.92	.306	7.77	3,840	5,521	22.49	10.20	32.34	14.67
88H23	.880	22.35	.860	21.84	9/16	14.29	.248	6.30	.306	7.77	3,200	3,850	19.88	9.02	23.91	10.85
88H23_AUTO	.880	22.35	.860	21.84	9/16	14.29	.242	6.15	.306	7.77	3,200	3,850	21.93	9.95	26.39	11.97
88H23_C	.880	22.35	.860	21.84	9/16	14.29	.228	5.79	.306	7.77	3,200	3,850	21.93	9.95	26.39	11.97
88H23_G	.880	22.35	.860	21.84	9/16	14.29	.242	6.15	.306	7.77	3,200	3,850	21.93	9.95	26.39	11.97
90A29_G	.900	22.86	.430	10.92	15/32	11.90	.302	7.67	.410	10.41	--	8,800	--	--	52.04	23.61
90F18R	.900	22.86	.735	18.67	5/8	15.88	.196	4.98	.260	6.60	--	5,210	--	--	31.21	14.16
90F18S	.900	22.86	.735	18.67	5/8	15.88	.202	5.13	.260	6.60	3,948	--	21.43	9.72	--	--
90F18_G	.900	22.86	.735	18.67	5/8	15.88	.196	4.98	.260	6.60	3,948	5,210	23.65	10.73	31.21	14.16
90H17	.900	22.86	.860	21.84	5/8	15.88	.186	4.72	.260	6.60	3,290	4,480	26.66	12.09	36.31	16.47
90H17_LP	.900	22.86	.860	21.84	5/8	15.88	.177	4.50	.260	6.60	3,290	4,480	26.66	12.09	36.31	16.47
90H18	.900	22.86	.860	21.84	5/8	15.88	.196	4.98	.260	6.60	3,290	4,480	23.06	10.46	31.48	14.28
90H18_BP	.900	22.86	.860	21.84	5/8	15.88	.198	5.03	.260	6.60	9,000	--	61.11	27.72	--	--
90H18_C	.900	22.86	.860	21.84	5/8	15.88	.180	4.57	.260	6.60	3,290	4,480	23.78	10.79	32.38	14.69
90H18_L	.900	22.86	.860	21.84	5/8	15.88	.186	4.72	.260	6.60	3,290	4,480	23.78	10.79	32.38	14.69
95F23	.938	23.83	.735	18.67	21/32	16.67	.238	6.05	.306	7.77	3,360	4,375	22.29	10.11	29.02	13.16
95F23_C	.938	23.83	.735	18.67	21/32	16.67	.224	5.69	.306	7.77	3,360	4,375	22.29	10.11	29.02	13.16
96A23	.960	24.38	.430	10.92	19/32	15.08	.234	5.94	.306	7.77	5,600	10,000	23.55	10.68	42.06	19.08
97H18	.970	24.64	.860	21.84	5/8	15.88	.194	4.93	.260	6.60	3,290	4,585	25.63	11.63	35.72	16.20
97H18_L	.970	24.64	.860	21.84	5/8	15.88	.125	3.18	.260	6.60	3,290	4,585	25.63	11.63	35.72	16.20
98H22_P-BLK	.980	24.89	.860	21.84	21/32	16.67	.226	5.74	.306	7.77	2,800	3,900	26.05	11.82	36.28	16.46
98H22_P-WHT	.980	24.89	.860	21.84	21/32	16.67	.226	5.74	.306	7.77	2,800	3,900	26.05	11.82	36.28	16.46
101F23	1.010	25.65	.735	18.67	21/32	16.67	.238	6.05	.306	7.77	3,360	4,350	24.00	10.89	31.07	14.09
101F23_A	1.010	25.65	.735	18.67	21/32	16.67	.238	6.05	.306	7.77	3,360	--	10.65	4.83	--	--
101H22	1.010	25.65	.860	21.84	11/16	17.46	.230	5.84	.306	7.77	2,800	3,900	26.15	11.86	36.43	16.52
101H23	1.010	25.65	.860	21.84	11/16	16.67	.240	6.10	.306	7.77	2,800	3,900	22.71	10.30	31.64	14.35
101H23_C	1.010	25.65	.860	21.84	11/16	17.46	.226	5.74	.306	7.77	2,800	3,900	22.71	10.30	31.64	14.35
101H23_L	1.010	25.65	.860	21.84	11/16	17.46	.232	5.89	.306	7.77	2,800	3,900	22.71	10.30	31.64	14.35
102A25	1.020	25.91	.430	10.92	5/8	15.88	.246	6.25	.326	8.28	--	9,375	--	--	43.06	19.53
109H22	1.090	27.69	.860	21.84	23/32	18.26	.228	5.79	.306	7.77	2,400	3,900	24.83	11.26	40.35	18.30
109H22_C	1.090	27.69	.860	21.84	23/32	18.26	.216	5.49	.306	7.77	2,400	3,900	24.19	10.97	39.52	17.93
109H22_L	1.090	27.69	.860	21.84	23/32	18.26	.218	5.54	.306	7.77	2,400	3,900	25.47	11.55	41.38	18.77
110A18	1.100	27.94	.430	10.92	21/32	16.67	.202	5.13	.260	6.60	6,580	9,300	25.54	11.58	36.10	16.37
110E25_S4	1.100	27.94	.670	17.02	23/32	18.26	.232	5.89	.326	8.28	1,443	--	10.23	4.64	--	--
110H24	1.100	27.94	.860	21.84	23/32	18.26	.248	6.30	.326	8.28	2,220	3,750	23.18	10.51	39.15	17.76
110H25	1.100	27.94	.860	21.84	23/32	18.26	.252	6.40	.326	8.28	2,220	3,750	20.21	9.17	34.13	15.48
110H25_C	1.100	27.94	.860	21.84	23/32	18.26	.238	6.05	.326	8.28	2,220	3,750	20.21	9.17	34.13	15.48
112D25	1.120	28.45	.620	15.75	23/32	18.26	.258	6.55	.326	8.28	3,108	--	20.77	9.42	--	--
114D24	1.140	28.96	.620	15.75	3/4	19.05	.247	6.27	.326	8.28	3,108	--	24.55	11.14	--	--
116F33	1.160	29.46	.735	18.67	11/16	17.46	.330	8.38	.398	10.11	2,160	--	17.72	8.04	--	--
120H23_C	1.200	30.48	.860	21.84	3/4	19.05	.224	5.69	.306	7.77	2,400	--	23.83	10.81	--	--
125A38_G	1.250	31.75	.430	10.92	11/16	17.46	.280	7.11	.480	12.19	3,000	5,100	27.38	12.42	46.55	21.12
125A38_S3	1.250	31.75	.430	10.92	11/16	17.46	.360	9.14	.480	12.19	3,000	5,100	27.38	12.42	46.55	21.12

CLIP	LENGTH		WIDTH		HEIGHT		INSIDE		OUTSIDE		CLIPS/ CTN	CLIPS/ ROLL	WT./CTN		WT./ROLL	
	IMP	MET	IMP	MET	IMP	MET	IMP	MET	IMP	MET			LBS	KG	LBS	KG
132A38_G	1.320	33.53	.430	10.92	3/4	19.05	.360	9.14	.480	12.19	3,000	5,100	28.91	13.11	49.15	22.29
132A38_S3	1.320	33.53	.430	10.92	3/4	19.05	.380	9.65	.500	12.70	3,000	5,100	29.22	13.25	49.67	22.53
132A38_S4	1.320	33.53	.430	10.92	3/4	19.05	.380	9.65	.500	12.70	3,000	5,100	28.91	13.11	49.15	22.29
135H30_C	1.350	34.29	.860	21.84	13/16	20.64	.298	7.57	.388	9.86	1,550	2,350	19.35	8.78	29.34	13.31
135H31	1.350	34.29	.860	21.84	13/16	20.64	.316	8.03	.388	9.86	1,550	2,350	18.83	8.54	27.80	12.61
Should you not see the clip you are looking for, please contact us.																